



ST312



ST818

## INDEX

OTR TIRE .....	2-3
OTR GRADER TIRE .....	4-5
PORT USE TIRE .....	5
OTR RADIAL TIRE .....	6
FORTLIFT LIFT TIRE .....	6
INDUSTRIAL TIRE .....	7-9
SKID STEER TIRE .....	10
FARM TIRE .....	11
IMPLEMENT TIRE .....	12
AGRICULTURAL TIRE .....	13-17
AGRICULTURAL RADIAL TIRE .....	15-16
IRRIGATION TIRE .....	17
RUBBER MINE TIRE .....	18
FORESTRY TIRE .....	19-20
FLOTATION TIRE .....	20
LPT & MOBILE HOME TIRE .....	21
TRAILER TIRE .....	22-24
BIAS TRUCK TIRE .....	24-26
MINING TIRE .....	25
UNDERGROUND MINING TIRES .....	26

### OTR TIRE E3/L3 / ST312

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
16.00-25	28	TL	11.25	30	38	432	17.0	1493	58.8	575*750	83*109	6700*11500	14800*25400	50*10	30*5
16.00-25	32	TL	11.25	30	38	432	17.0	1493	58.8	625*800	90*116	7200*12100	15875*26675	50*10	30*5
18.00-25	32	TT/TL	13.00	32	40	498	19.6	1617	63.7	575*750	83*109	8750*15000	19300*33100	50*10	30*5
18.00-25	40	TL	13.00	32	40	498	19.6	1617	63.7	700*950	101*138	9700*21385	17000*37480	50*10	30*5
17.5-25	16	TT/TL	14.00/1.5	25.5	32	445	17.5	1348	53.1	300*475	44*69	4250*7300	9350*16100	50*10	30*5
17.5-25	20	TT/TL	14.00/1.5	25.5	32	445	17.5	1348	53.1	400*575	58*83	5000*8250	11000*18200	50*10	30*5
20.5-25	20	TT/TL	17.00/2.0	29	37	521	20.5	1493	58.8	325*450	47*65	6000*9500	13200*20900	50*10	30*5
20.5-25	24	TT/TL	17.00/2.0	29	37	521	20.5	1493	58.8	350*525	51*76	6300*10300	13890*22700	50*10	30*5
23.5-25	20	TT/TL	19.50/2.5	32	40	597	23.5	1617	63.7	300*375	44*54	7300*10900	16100*24000	50*10	30*5
23.5-25	24	TT/TL	19.50/2.5	32	40	597	23.5	1617	63.7	350*475	51*69	8000*12500	17600*27600	50*10	30*5
26.5-25	28	TL	22.00/3.0	35	44	673	26.5	1750	68.9	350*475	51*69	10000*15500	22000*34200	50*10	30*5
29.5-25	28	TL	25.00/3.5	36	45	749	29.5	1874	73.8	325*425	47*62	11500*17500	25400*38600	50*10	30*5

### OTR TIRE E3/L3 / ST818

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
23.5-25	20	TT/TL	19.50/2.5	31.5	39.5	597	23.5	1617	63.7	300*375	44*54	7300*10900	16100*24000	50*10	30*5
23.5-25	24	TT/TL	19.50/2.5	31.5	39.5	597	23.5	1617	63.7	350*475	51*69	8000*12500	17600*27600	50*10	30*5



## OTR TIRE E3/L3 / ST313

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
23.5-25	20	TT/TL	19.50/2.5	31.5	39.5	597	23.5	1617	63.7	300*375	44*54	7300*10900	16100*24000	50*10	30*5
23.5-25	24	TT/TL	19.50/2.5	31.5	39.5	597	23.5	1617	63.7	350*475	51*69	8000*12500	17600*27600	50*10	30*5

## OTR TIRE E3/L3 / ST314

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
14.00-24	24	TT	10.00	25	32	375	14.8	1368	53.9	575	83	5150	11400	50	30

## OTR TIRE JY628

Size	P.R.	TT/TL	Rim	Tread	New tire inflated dimensions		Pressure		Max. Load	
					Section Width (mm)	Overall Diameter (mm)	(kPa)	(psi)	(kg)	(Lbs)
17.5-25	28	TT	14.00/1.5	L5	445	1400	475	69	7300	16100
18.00-25	40	TT	13.00/2.5	L5	495	1615	950	138	17000	37480
20.5-25	20	TT	17.00/2.0	L5	521	1548	450	65	9500	20900
20.5-25	24	TT	17.00/2.0	L5	521	1548	525	76	10300	22700
23.5-25	24	TT	19.50/2.5	L5	595	1675	475	69	12500	27600
23.5-25	28	TT	19.50/2.5	L5	595	1675	550	80	13600	29980
26.5-25	28	TT	22.00/3.0	L5	650	1750	475	69	15500	34200
26.5-25	32	TT	22.00/3.0	L5	650	1750	550	80	17000	37500
29.5-25	28	TT	25.00/3.5	L5	749	1921	425	62	17500	38600
29.5-25	34	TT	25.00/3.5	L5	749	1921	525	76	20000	44090
16/70-16	14	TT	10.00	L5	385	935	280	41	1600	3525
16/70-20	16	TT	13.00	L5	410	1075	300	43.5	3350	7385
20.5/70-16	14	TT	10.00	L5	385	935	280	41	1600	3525



G2/L2-A/ST518

G2/L2-B/ST519

G2/L2-C/ST316

## OTR GRADER TIRE G2/L2-A/ST518 , B/ST519

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
13.00-24	12	TL	8.00	24.5	31	333	13.1	1278	50.3	300*450	44*65	2725*5600	6000*12300	40*10	25*5
13.00-24	14	TL	8.00	24.5	31	333	13.1	1278	50.3	525	76	6000	13200	10	5
13.00-24	16	TL	8.00	24.5	31	333	13.1	1278	50.3	400*600	58*87	3200*6500	7050*14300	40*10	25*5
14.00-24	12	TL	8.00	25.5	32	362	14.3	1348	53.1	325*425	47*62	3450*6300	7600*13900	40*10	25*5
14.00-24	16	TL	8.00	25.5	32	362	14.3	1348	53.1	375*550	54*80	3650*7300	8050*16100	40*10	25*5

## OTR GRADER TIRE G2/L2-C/ST316

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
15.5-25	12	TL	12.00/1.3	25	32	394	15.5	1278	50.3	250	36	2650	5840	40	25
17.5-25	12	TL	14.00/1.5	25	32	445	17.5	1348	53.1	200	29	2900	6400	40	25
17.5-25	16	TL	14.00/1.5	25	32	445	17.5	1348	53.1	275	40	3350	7400	40	25
20.5-25	16	TL	17.00/2.0	26.5	33	521	20.5	1493	58.8	225	33	4000	8800	40	25
20.5-25	20	TL	17.00/2.0	26.5	33	521	20.5	1493	58.8	275	40	4500	9900	40	25



G3/L3



E4

## OTR GRADER TIRE G3/L3

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	inch	(mm)	inch						
14.00-24TG	16	TL	10.00	25	32	375	14.8	1368	53.8	350	50	3650	8030	40	25
14.00-24TG	16	TL	10.00	25	32	375	14.8	1368	53.8	550	80	7300	16100	10	5

## PORT USE TIRE E4

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	inch	(mm)	inch						
12.00-20	24	TT	8.50	45	57	315	12.4	1146	45.1	1000	145	9800	21600	50	30



L3/HT618



## OTR RADIAL TIRE L3/HT618

Size	TT/TL	Load Index	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	inch	(mm)	inch						
17.5R25	TL	★★	14.00	26	33	445	17.5	1348	53.1	650	94	8500	18700	10	5
20.5R25	TL	★★	17.00	28.5	36	521	20.5	1493	58.8	650	94	11500	25400	10	5
23.5R25	TL	★★	19.50	32	40	597	23.5	1617	63.7	650	94	14500	32000	10	5
26.5R25	TL	★★	22.00	35	44	673	26.5	1750	68.9	650	94	18500	40800	10	5
29.5R25	TL	★★	25.00	38	48	749	29.5	1874	73.8	650	94	22400	49400	10	5

## FORKLIFT TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	inch	(mm)	inch						
6.50-10NHS	10	TT	5.00	12	15	175	6.9	597	23.5	790	115	1400	3085	25	15
28X9-15/8.15-15	14	TT	7.00	16.5	21	221	8.7	706	27.8	970	140	3050	6720	25	15
7.00-12NHS	14	TT	5.00	14.5	18	190	7.5	676	26.6	1000	145	2590	5710	25	15
8.25-15NHS	16	TT	6.50	16	20	236	9.3	847	33.3	925	134	4050	8925	25	15
5.00-8NHS	10	TT	3.50	10	13	137	5.4	470	18.5	1000	145	1150	2535	25	15.5
6.00-9NHS	10	TT	4.00	12	15	160	6.3	540	21.3	860	125	1505	3315	25	15.5
6.50-10NHS	12	TT	5.00	12	15	175	6.9	590	23.2	1000	145	1895	4170	25	15.5
7.00-12NHS	12	TT	5.00	14.5	18	190	7.5	676	26.6	860	125	2375	5235	25	15.5
8.25-15NHS	14	TT	6.50	16	20	235	9.3	840	33.1	830	120	3775	8320	25	15.5
18x7-8NHS	14	TT	4.33	12	15	173	6.8	465	18.3	970	140	1505	3315	25	15.5
23x9-10NHS	16	TT	6.50	12	15	225	8.9	595	23.4	1030	150	2810	6195	25	15.5



## INDUSTRIAL TRACTORS

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
<b>F3</b>															
11L-16SL	12	TL	8.00	11	14	279	10.8	838	34.8	440	64	1250	2760	40	25
<b>F-3</b>															
11L-16	16	TL	8.00	12.7	16	279	11.00	838	31.82	525	76	1450	3195	40	25
<b>L4</b>															
11L-16SL	12	TL	8.00	16	20	279	12.1	838	38.0	440	64	1250	2760	40	25



## INDUSTRIAL TRACTORS

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
					(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
<b>NT198</b>																
16.9-28	16	TL	R4	15.00	24	30	429	16.9	1427	56.2	280	40	3700	8155	40	25
<b>R4</b>																
340/80R18		TL	R4	11.00	23.8	30	333	13.1	1008	39.7	320	46	2240	4940	50	30
500/75R24		TL	R4	16.00	27	34	495	19.5	1310	51.6	320	46	4125	9100	50	30



## INDUSTRIAL TRACTORS

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
<b>R4</b>															
10.5/80-18	10	TL	9.00	22	28	274	10.8	885	34.8	370	54	1950	4295	40	25
12.5/80-18	12	TL	9.00	27	34	308	12.1	965	38.0	370	54	2650	5840	40	25
12.5/80-18	14	TL	9.00	27	34	308	12.1	965	38.0	420	61	2850	6280	40	25
12.5/80-18	16	TL	9.00	27	34	308	12.1	965	38.0	490	71	3150	6945	40	25
<b>L5</b>															
11L-16	14	TL	8.00	35	44	280	11.0	845	33.3	470	68	1550	3415	40	25
12.5/80-18	14	TL	9.00	27	34	308	12.1	965	38.0	420	61	2850	6280	40	25
12.5/80-18	16	TL	9.00	27	34	308	12.1	965	38.0	490	71	3150	6945	40	25



## INDUSTRIAL TRACTORS

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
16.9-24	12	TL	15.00	27	34	429	16.9	1309	51.5	260	37	3250	7150	40	25
16.9-24	16	TL	15.00	27	34	429	16.9	1309	51.5	280	40	3600	7935	40	25
16.9-28	12	TL	15.00	33	35	429	16.9	1427	56.2	260	37	3550	7850	40	25
16.9-28	16	TL	15.00	33	30	429	16.9	1427	56.2	280	40	3700	8155	40	25
18.4-26	12	TL	16.00	28	35	467	18.4	1426	56.1	210	30	2900	6400	40	25
18.4-26	16	TL	16.00	28	35	467	18.4	1426	56.1	240	35	3200	7055	40	25
18.4-28	12	TL	16.00	39	49	467	18.4	1500	59.1	250	36	4000	8800	40	25
18.4-28	16	TL	16.00	39	49	467	18.4	1500	59.1	270	39	4250	9370	40	25



B/ST516

## INDUSTRIAL TRACTORS R4

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
17.5L-24	12	TL	15.00	25	32	445	17.5	1241	48.9	190	28	1725	3800	40	25
19.5L-24	12	TL	17.00	26	33	495	19.5	1339	52.7	230	34	3450	7600	40	25
21L-24	12	TL	18.00	27	34	533	21.0	1378	54.3	220	32	3875	8550	40	25



A/ST515



C/ST517



D/L5

## INDUSTRIAL TRACTORS R4

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
<b>R4-A/ST515</b>															
19.5L-24	12	TL	17.00	26	33	495	19.5	1339	52.7	230	34	3450	7600	40	25
19.5L-24	14	TL	17.00	26	33	495	19.5	1339	52.7	275	40	2800	6170	40	25
<b>R4-C/ST517</b>															
19.5L-24	12	TL	17.00	27.5	35	495	19.5	1339	52.7	230	34	3450	7600	40	25
19.5L-24	14	TL	17.00	26	33	495	19.5	1339	52.7	275	40	2800	6170	40	25
<b>R4-D/L5</b>															
19.5L-24	14	TL	17.00	38	48	495	19.5	1340	52.8	275	40	2800	6170	40	25
19.5L-24	16	TL	17.00	38	48	495	19.5	1340	52.8	310	45	3500	7715	40	25



SKS-1



SKS-2(L4)



SKS-4(KL4)



SKS-5(L5)

## SKID STEER TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
<b>SKS-1</b>															
10-16.5	10	TL	8.25	18	23	264	10.4	773	30.4	520	75	2135	4710	10	5
10-16.5	12	TL	8.25	18	23	264	10.4	773	30.4	620	90	2375	5240	10	5
12-16.5	12	TL	9.75	18	23	307	12.1	831	32.7	550	80	2865	6315	10	5
12-16.5	14	TL	9.75	18	23	307	12.1	831	32.7	620	90	3075	6780	10	5
14-17.5	14	TL	10.5	20	25	349	13.7	921	36.3	550	80	3875	8540	10	5
15-19.5	14	TL	11.75	20	25	389	15.3	1019	40.1	485	70	4565	10060	10	5
<b>SKS-2(L4)</b>															
10-16.5	10	TL	8.25	18	23	264	10.4	773	30.4	520	75	2135	4710	10	5
10-16.5	12	TL	8.25	18	23	264	10.4	773	30.4	620	90	2375	5240	10	5
12-16.5	12	TL	9.75	18	23	307	12.1	831	32.7	550	80	2865	6315	10	5
12-16.5	14	TL	9.75	18	23	307	12.1	831	32.7	620	90	3075	6780	10	5
14-17.5	14	TL	10.5	20	25	349	13.7	921	36.3	550	80	3875	8540	10	5
15-19.5	14	TL	11.75	20	25	389	15.3	1019	40.1	485	70	4565	10060	10	5
<b>SKS-4(KL4)</b>															
10-16.5	10	TL	8.25	18	23	264	10.4	773	30.4	520	75	2135	4710	10	5
10-16.5	12	TL	8.25	18	23	264	10.4	773	30.4	620	90	2375	5240	10	5
12-16.5	12	TL	9.75	18	23	307	12.1	831	32.7	550	80	2865	6315	10	5
12-16.5	14	TL	9.75	18	23	307	12.1	831	32.7	620	90	3075	6780	10	5
14-17.5	14	TL	10.5	20	25	349	13.7	921	36.3	550	80	3875	8540	10	5
15-19.5	14	TL	11.75	20	25	389	15.3	1019	40.1	485	70	4565	10060	10	5
<b>SKS-5(L5)</b>															
10-16.5	12	TL	8.25	34	43	264	10.4	805	31.7	620	90	2375	5240	10	5
12-16.5	14	TL	9.75	35	44	312	12.3	835	32.9	620	90	3075	6780	10	5
14-17.5	14	TL	10.50	35	44	349	13.7	921	36.3	550	80	3875	8540	10	5



F2/3RIB

F2/4RIB

F2

T239

## FARM TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
<b>F2/3RIB</b>															
7.5L-15	8	TT /TL	6.00	17	21	208	8.2	745	29.3	370	53	840	1850	40	25
9.5L-15	8	TT /TL	7.00	20	25	240	9.4	780	30.7	330	48	850	1870	40	25
11L-15	8	TT /TL	8.00	19	24	280	11.0	810	31.9	300	44	950	2090	40	25
6.00-16SL	6	TT /TL	4.00	17	21	159	6.3	739	29.1	360	52	515	6005	40	25
7.50-16SL	8	TT /TL	5.50	20	25	203	8.0	808	31.8	385	56	775	1705	40	25
<b>F2/4RIB</b>															
10.00-16SL	10	TT /TL	8.00	25	32	274	10.8	894	35.2	300	44	1120	2480	40	25
11.00-16SL	12	TT /TL	10.00	24	30	315	12.4	967	38.1	410	60	1550	3420	40	25
<b>F2</b>															
7.50-16	14	TL	5.50	14	18	203	8.0	808	31.8	470	68	980	2160	40	25
10.00-16	14	TL	8.00	20.6	26	274	10.8	894	35.2	360	52	1160	2555	40	25
11.00-16	14	TL	10.00	23	29	315	12.4	967	38.1	440	64	1600	3525	40	25

## TRACTION TYPE TRAILER TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
<b>T239</b>															
9.00-16	16	TT /TL	6.00F	16.5	21	245	9.6	890	35.0	500	72	1833	4040	30	20



I1

IMP-01

R1

## IMPLEMENT TIRE I1

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
9.5L-15SL	8	TL	7.00	7.5	9	241	9.5	767	30.2	300	53	1120	2470	40	25
9.5L-15SL	12	TL	7.00	7.5	9	241	9.5	767	30.2	440	64	1450	3200	40	25
11L-15SL	8	TL	8.00	7.5	9	279	11.0	777	30.6	250	44	1150	2540	40	25
11L-15SL	12	TL	8.00	7.5	9	279	11.0	777	30.6	360	52	1450	3200	40	25
12.5L-15SL	12	TL	10.00	7.5	9	318	12.5	823	32.4	360	52	1750	3860	40	25

## IMPLEMENT & TRAILER TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
					(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
10.0/75-15.3	10	TL	IMP-01	9.00	9	11	264	10.4	760	29.9	390	57	1550	3415	40	25
10.0/75-15.3	12	TL	IMP-01	9.00	9	11	264	10.4	760	29.9	470	68	1550	3415	40	25
11.5/80-15.3	12	TL	IMP-01	9.00	10	13	290	11.4	845	33.3	410	59	2180	4805	40	25
11.5/80-15.3	14	TL	IMP-01	9.00	10	13	290	11.4	845	33.3	475	69	2430	5355	40	25
12.5/80-15.3	14	TL	IMP-01	9.00	10.5	13	307	12.1	889	35.0	430	62	2650	5840	40	25
12.5/80-15.3	16	TL	IMP-01	9.00	10.5	13	307	12.1	889	35.0	490	71	2820	6215	40	25

## MPT TIRE R1

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
10.0/75-15.3	8	TL	9.00	25	32	264	10.4	760	29.9	310	44	950	2100	40	25
10.0/75-15.3	10	TL	9.00	25	32	264	10.4	760	29.9	390	56	1090	2400	40	25
10.0/75-15.3	12	TL	9.00	25	32	264	10.4	760	29.9	470	68	1180	2600	40	25
11.5/80-15.3	8	TL	9.00	25	32	290	11.4	845	33.3	270	39	1180	2600	40	25
11.5/80-15.3	12	TL	9.00	25	32	290	11.4	845	33.3	340	49	1360	3000	40	25
11.5/80-15.3	14	TL	9.00	25	32	290	11.4	845	33.3	475	69	1700	3745	40	25



## AGRICULTURE TIRE R1-1

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	inch	(mm)	inch						
5.00-15	6	TL	4.00	15	19	130	5.1	640	25.2	350	50	455	1005	40	25
7.50-16	6	TT/TL	5.50	26	33	205	8.1	810	31.9	210	30	650	1430	40	25

## AGRICULTURE TIRE R1-2

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	inch	(mm)	inch						
12.4-24	8	TT/TL	11.00	36	45	315	12.4	1159	45.6	220	32	1285	2830	40	25
12.4-24	12	TT/TL	11.00	36	45	315	12.4	1159	45.6	330	48	1600	3520	40	25
13.6-24	8	TT/TL	12.00	36	45	345	13.6	1210	47.6	190	28	1400	3080	40	25
13.6-24	12	TT/TL	12.00	36	45	345	13.6	1210	47.6	250	36	1790	3945	40	25
14.9-24	8	TT/TL	13.00	36	45	378	14.9	1265	49.8	180	26	1600	3520	40	25
14.9-24	12	TT/TL	13.00	36	45	378	14.9	1265	49.8	260	38	2000	4400	40	25
14.9-28	8	TT/TL	13.00	36	45	378	14.9	1367	53.8	180	26	1700	3740	40	25
14.9-28	12	TT/TL	13.00	36	45	378	14.9	1367	53.8	250	36	2120	4670	40	25

## AGRICULTURE TIRE R1-3

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	inch	(mm)	inch						
23.1-26	12	TT/TL	20.00	40	50	587	23.1	1605	63.2	165/170	24	3250	7150	40	25
16.9-30	10	TT/TL	15.00	37	47	429	16.9	1485	58.5	165	24	2000	4400	40	25
18.4-30	10	TT/TL	16.00	37.5	47	467	18.4	1552	61.1	180	26	2500	5510	40	25
18.4-30	12	TT/TL	16.00	37.5	47	467	18.4	1552	61.1	220	32	2900	6400	40	25
18.4-34	10	TT/TL	16.00	37.5	47	467	18.4	1654	65.1	180	26	2725	6000	40	25
18.4-34	12	TT/TL	16.00	37.5	47	467	18.4	1654	65.1	220	32	3000	6600	40	25
15.5-38	8	TT/TL	14.00	37.5	47	394	15.5	1569	61.8	180	26	1850	4075	40	25
15.5-38	10	TT/TL	14.00	37.5	47	394	15.5	1569	61.8	220	32	2100	4630	40	25
18.4-38	10	TT/TL	16.00	37.5	47	467	18.4	1802	70.9	180	26	2900	6400	40	25
18.4-38	12	TT/TL	16.00	37.5	47	467	18.4	1802	70.9	220	32	3250	7150	40	25

## AGRICULTURE TIRES R1W

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
					(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
							(mm)	inch	(mm)	inch						
11.2-24	12	TT	R1W	10.00	40	50	284	11.2	1103	43.4	330	48	1450	3195	40	25
12.4-24	12	TT	R1W	11.00	40	50	315	12.4	1159	45.62	330	48	1600	3520	40	25
13.6-24	12	TT	R1W	12.00	43	54	345	13.6	1210	47.6	250	36	1790	3945	40	25
14.9-24	12	TT	R1W	13.00	45	57	378	14.9	1265	49.8	260	38	2000	4400	40	25
16.9-30	12	TT	R1W	15.00	45	57	429	16.9	1485	58.48	230	34	2500	5520	40	25
14.9-38	12	TT	R1W	13.00	43	54	378	14.9	1621	63.8	250	36	2130	4695	40	25
18.4-30	12	TT	R1W	16.00	45	57	467	18.4	1552	61.1	220	32	2900	6400	40	25
18.4-34	12	TT	R1W	16.00	45	57	467	18.4	1654	65.1	220	32	3000	6600	40	25
18.4-38	12	TT	R1W	16.00	45	57	467	18.4	1802	70.9	220	32	3250	7150	40	25
15.5-38	12	TT	R1W	14.00	40	50	394	15.5	1569	61.8	240	35	2350	5180	40	25
30.5L-32	18	TL	R1W	27.00	52	65	775	30.5	1819	71.6	190	28	5250	11575	40	25
14.9-28	12	TT	R1W	13.00	45	57	378	14.9	1367	53.82	250	36	2120	4670	40	25
16.9-28	12	TT	R1W	15.00	45	57	429	16.9	1435	56.48	300	44	3875	8540	40	25
16.9-38	14	TT	R1W	15.00	45	56	429	16.9	1689	66.5	250	36	2750	6060	40	25
18.4-26	12	TT	R1W	16.00	45	57	467	18.4	1450	57.10	220	32	2650	5840	40	25
20.8-34	14	TT	R1W	18.00	48	61	528	20.8	1732	68.2	220	32	3725	8210	40	25
20.8-38	14	TT	R1W	18.00	48	60	528	20.8	1834	72.20	220	32	3875	8550	40	25
16.9-24	12	TT	R1W	15.00	45	57	429	16.90	1333	52.48	230	34	2300	5080	40	25
16.9-34	12	TT	R1W	15.00	45	57	429	16.90	1587	62.48	230	34	2720	5995	40	25
24.5-32	16	TL	R1W	21.00	50	63	622	24.50	1803	71.00	210	30	4500	9900	40	25
18.4-42	14	TL	R1W	16.00	45	57	467	18.40	1857	73.10	250	36	3650	8050	40	25
18.4-46	16	TL	R1W	16.00	45	57	467	18.40	1958	77.10	320	46	4475	9865	40	25



R2



R1W/HT616

## AGRICULTURE TIRE R2

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	(inch)	(mm)	(inch)						
12.4-24	10	TT	W11	60	75	315	12.4	1192	46.9	260	38	1450	3195	40	25
14.9-24	10	TT	W13	69	87	378	14.9	1305	51.4	220	32	1800	3960	40	25
14.9-28	10	TT	W13	69	87	378	14.9	1406	55.4	220	32	1900	4180	40	25
23.1-26	12	TT	DW20	80	100	587	23.1	1662	65.4	170	25	3250	7150	40	25
18.4-30	10	TT	W16L	90	113	467	18.4	1599	63.0	180	26	2500	5520	40	25
18.4-30	12	TT	W16L	90	113	467	18.4	1599	63.0	220	32	2900	6400	40	25
18.4-34	10	TT	W16L	90	113	467	18.4	1701	67.0	180	26	2725	6000	40	25
18.4-34	12	TT	W16L	90	113	467	18.4	1701	67.0	220	32	3000	6600	40	25
18.4-38	10	TT	W16L	90	113	467	18.4	1802	70.9	180	26	2900	6400	40	25
18.4-38	12	TT	W16L	90	113	467	18.4	1802	70.9	220	32	3250	7150	40	25

## AGRICULTURE RADIAL TIRES R1W

Size	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Load Index	Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter			(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	(inch)	(mm)	(inch)							
340/85R28	TL	R1W	11.00	44	55	343	13.5	1289	50.7	125A8	160	23	1750	3850	40	25
380/85R30	TL	R1W	12.00	45	57	380	14.9	1408	55.4	135A8	160	23	2180	4800	40	25
420/85R28	TL	R1W	13.00	48	60	418	16.5	1425	56.0	139A8	160	23	2430	5360	40	25
420/85R30	TL	R1W	13.00	48	60	418	16.5	1476	58.1	140A8	160	23	2500	5510	40	25
540/65R28	TL	R1W	18.00	46	58	550	21.5	1413	55.6	142A8	160	23	2650	5840	40	25
540/65R30	TL	R1W	18.00	46	58	550	21.5	1464	57.6	143A8	160	23	2725	6005	40	25
460/85R30	TL	R1W	14.00	48	60	455	18.4	1544	60.8	145A8	160	23	2900	6395	40	25
460/85R34	TL	R1W	14.00	48	60	455	18.4	1646	64.8	147A8	160	23	3075	6780	40	25
460/85R38	TL	R1W	14.00	48	60	455	18.4	1747	68.8	149A8	160	23	3250	7165	40	25
380/85R28	TL	R1W	12.00	45	57	380	14.9	1357	53.4	133A8	160	23	2060	4540	40	25
400/75R38	TL	R1W	13.00	42	53	404	15.5	1565	61.6	138A8	160	23	2360	5200	40	25



R1W/HT616

## AGRICULTURE RADIAL TIRES R1W

Size	TT/TL	PATTERN	Rim	New tire inflated dimensions				Pressure		Max. Load		Speed
				Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	
				(mm)	(inch)	(mm)	(inch)					
280/85R20	TL	R1W	W10	283	11.1	984	38.7	160	23	1120	2470	A8/B
280/85R24	TL	R1W	W10	282	11.1	1086	42.8	160	23	1215	2680	A8/B
300/95R46	TL	R1W	W9	305	12.0	1717	67.6	400	58	3150	6945	A8/B
320/85R24	TL	R1W	W10	319	12.6	1154	45.4	160	23	1500	3310	A8/B
320/85R28	TL	R1W	W10	319	12.6	1255	49.4	160	23	1600	3530	A8/B
320/85R36	TL	R1W	W11	328	12.9	1455	57.3	160	23	1800	3970	A8/B
320/90R46	TL	R1W	W10	312	12.3	1744	68.7	400	58	3150	6945	A8/B
340/85R24	TL	R1W	W11	343	13.5	1188	46.8	160	23	1500	3310	A8/B
380/85R24	TL	R1W	W12	380	15.0	1256	49.4	160	23	1950	4300	A8/B
380/85R28	TL	R1W	W12	380	15.0	1357	53.4	160	23	2060	4540	A8/B
380/80R38	TL	R1W	W12	380	15.0	1573	61.9	160	23	2120	4670	A8/B
380/90R46	TL	R1W	W12	380	15.0	1852	72.9	240	35	3250	7165	A8/B
380/70R24	TL	R1W	W12	380	15.0	1190	46.9	160	23	1650	3640	A8/D
420/70R24	TL	R1W	W13	418	16.5	1248	49.1	160	23	1900	4190	A8/B
420/70R28	TL	R1W	W13	418	16.5	1349	53.1	160	23	2060	4540	A8/D
420/85R34	TL	R1W	W13	418	16.5	1578	62.1	160	23	2650	5840	A8/B
480/70R24	TL	R1W	W15L	479	18.9	1316	51.8	400	58	4750	10470	A8/B
480/70R28	TL	R1W	W15L	479	18.9	1421	55.9	160	23	2500	5510	A8/D
480/70R30	TL	R1W	W15L	479	18.9	1478	58.2	160	23	2575	5680	A8/D
480/70R34	TL	R1W	W15L	479	18.9	1580	62.2	350	51	3875	8540	A8/D
480/80R46	TL	R1W	W15L	479	18.9	1936	76.2	240	35	4250	9370	A8/B
520/70R34	TL	R1W	W16L	516	20.3	1640	64.6	160	23	3150	6945	A8/D
520/70R38	TL	R1W	W16L	516	20.3	1749	68.9	160	23	3350	7385	A8/D
580/70R38	TL	R1W	W18L	577	22.7	1827	71.9	160	23	3875	8540	A8/D
520/85R38	TL	R1W	W18L	560	22.0	1857	73.1	160	23	3875	8540	A8/B
520/85R42	TL	R1W	DW18L	560	22.0	1969	77.5	160	23	4125	9090	A8/B
600/65R28	TL	R1W	W18L	591	23.3	1491	58.7	160	23	3075	6780	A8/B
620/70R42	TL	R1W	DW20B	625	24.6	1935	76.2	160	23	4500	9920	A8/D
650/65R42	TL	R1W	DW20A	645	25.4	1913	75.3	240	35	5150	11350	A8/D
650/65R38	TL	R1W	DW20A	645	25.4	1811	71.3	240	35	4875	10750	A8/B
710/70R42	TL	R1W	DW23A	716	28.2	2061	81.1	160	23	5600	12350	A8/D
710/70R38	TL	R1W	W23	716	28.2	1959	77.1	160	23	5300	11680	A8/B
800/65R32	TL	R1W	DW27B	798	31.4	1853	73.0	360	52	8250	18190	A8/B
IF600/70R30	TL	R1W	DW18L	591	23.3	1602	63.1	240	35	5150	11350	A8/D
VF380/90R46	TL	R1W	DW12	185	7.3	3855	151.8	440	64	6500	14330	D



R1

Irrigation R1

Non-Direction R1

## AGRICULTURE TIRE R1

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
13.6-38	8	TT	DW12A	34	43	345	13.6	1565	61.6	190	28	1700	3740	40	25
13.6-38	12	TT	DW12A	34	43	345	13.6	1565	61.6	290	42	2180	4800	40	25

## IRRIGATION TIRE R1

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
11.2-24	6	TT	10.00	25	32	284	11.2	1103	43.4	180	26	950	2090	40	25
11.2-24	8	TT	10.00	25	32	284	11.2	1103	43.4	250	36	1150	2540	40	25
11.2-38	6	TT	10.00	25	32	284	11.2	1459	57.4	180	26	1150	2530	40	25
11.2-38	8	TT	10.00	25	32	284	11.2	1459	57.4	220	32	1300	2865	40	25
14.9-24	6	TT	13.00	25	32	378	14.9	1265	49.8	180	26	1600	3520	40	25
14.9-24	8	TT	13.00	25	32	378	14.9	1265	49.8	230	34	1850	4080	40	25

## IRRIGATION TIRE R1 NON-DIRECTION

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
11.2-24	6	TT/TL	10.00	25	32	284	11.2	1103	43.4	180	26	950	2090	40	25
11.2-24	8	TT/TL	10.00	25	32	284	11.2	1103	43.4	250	36	1150	2540	40	25
11.2-38	6	TT/TL	10.00	25	32	284	11.2	1459	57.4	180	26	1150	2530	40	25
11.2-38	8	TT/TL	10.00	25	32	284	11.2	1459	57.4	220	32	1300	2865	40	25
14.9-24	6	TT/TL	13.00	25	32	378	14.9	1265	49.8	180	26	1600	3520	40	25
14.9-24	8	TT/TL	13.00	25	32	378	14.9	1265	49.8	230	34	1850	4080	40	25



L-6T+

L-6T+

MUD'R TP



L-6T+EXT

L-6s++EXT

## RUBBER MINE TIRE

Size	P.R.	TT/TL	Rim	Tread	New tire inflated dimensions				Pressure		Max. Load		Speed	
					Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
675*212-15	16	TL	6.00	L-6T+	209	8.2	689	27.1	415	60	2250	4960	10	5
850*350-16.5	42	TL	11.50	L-6T+	368	14.5	844	33.2	1170	170	4850	10690	10	5
850*350-15	42	TL	11.50	L-6T+	368	14.5	844	33.2	1170	170	4850	10690	10	5
875*375-15.1F	42	TL	11.50	L-6T+	375	14.8	859	33.8	1170	170	4850	10690	10	5
875*375-15.1F	48	TL	11.50	MUD'R TP	375	14.8	859	33.8	1310	190	5250	11575	10	5
875*375-16.5F	42	TL	11.50	L-6T+	375	14.8	859	33.8	1170	170	4850	10690	10	5
1385*490-650	60	TL	14.00	L-6s++ EXT	445	17.5	1400	55.1	575	83	8250	18200	10	5
1558*508-27.1	30	TL	11.25	L-6T+R EXT	432	17.0	1548	60.9	780	113	11800	26010	10	5
1000*500-16	48	TL	16.00	L-6T+ EXT	485	19.1	980	38.6	1200	174	5000	11020	10	5
1000*450-15.1F	48	TL	14.00	L-6T+ EXT	437	17.2	980	38.6	1150	167	4750	10470	10	5
1375*355-27.3	48	TL	10.00	L-6T+	375	14.8	1370	53.9	1300	188	13500	29760	10	5
1150x325-20	42	TL	8.50	L-6T+ EXT	315	12.4	1175	46.3	1300	188	12500	27555	10	5
1150x325-21	42	TL	8.50	L-6T+ EXT	315	12.4	1175	46.3	1300	188	12500	27555	10	5



## FORESTRY TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	inch	(mm)	inch						
16.9-30	10	TT/TL	W15L	48	60	210	8.3	1510	59.4	210	30.5	2575	5680	30	18.6
16.9-30	16	TT/TL	W15L	48	60	210	8.3	1510	59.4	300	43.5	3210	7080	30	18.6
18.4-26	10	TT/TL	DW16A	50	63	465	18.3	1475	58.1	170	24.7	2575	5680	30	18.6
18.4-26	16	TT/TL	DW16A	50	63	465	18.3	1475	58.1	280	40.6	3500	7720	30	18.6
18.4-30	10	TT/TL	DW16A	50	63	465	18.3	1575	62.0	170	24.7	2725	6010	30	18.6
18.4-30	16	TT/TL	DW16A	50	63	465	18.3	1575	62.0	280	40.6	3600	7940	30	18.6
18.4-34	12	TT/TL	DW16A	50	63	465	18.3	1680	66.1	210	30.5	3250	7165	30	18.6
18.4-34	16	TT/TL	DW16A	50	63	465	18.3	1680	66.1	280	40.6	3700	8160	30	18.6
23.1-26	14	TT/TL	DW20A	53	66	590	23.2	1630	64.2	210	30.5	4125	9090	30	18.6
23.1-26	16	TT/TL	DW20A	53	66	590	23.2	1630	64.2	240	34.8	4450	9810	30	18.6
24.5-32	16	TT/TL	DH21	55	69	625	24.6	1830	72.0	210	30.5	5000	11020	30	18.6
24.5-32	20	TT/TL	DH21	55	69	625	24.6	1830	72.0	280	40.6	5800	12790	30	18.6
DH35.5L-32	20	TT/TL	DH32	58	73	905	35.6	2004	78.9	240	34.8	6530	14400	30	18.6
DH35.5L-32	26	TT/TL	DH32	58	73	905	35.6	2004	78.9	280	40.6	8750	19290	30	18.6
73x44.00-32	16	TL	DH36	67	84	1153	45.4	1870	73.6	280	40.6	6900	15210	30	18.6
73x44.00-32	20	TL	DH36	67	84	1153	45.4	1870	73.6	340	49.3	8000	17640	30	18.6
30.5L-32	26	TL	27.00	55	69	775	30.50	1847	72.70	275	40	7100	15700	30	20
30.5L-32	26	TL	27.00	55	69	775	30.50	1847	72.70	310	45	10000	22000	10	5
28L-26	26	TL	25.00	56	71	714	28.10	1644	64.72	340	50	6050	13330	30	20
28L-26	26	TL	25.00	56	71	714	28.10	1644	64.72	380	55	8500	18735	10	5



## FORESTRY TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	inch	(mm)	inch						
500/60-26.5	20	TT/TL	AG 16.00	53	66	485	19.1	1265	49.8	500	72.5	5150	11350	40	24.9
600/50-22.5	20	TT/TL	AG 20.00	42	53	600	23.6	1170	46.1	550	79.8	4375	9645	40	24.9
600/55-26.5	20	TT/TL	AG 20.00	48	60	601	23.7	1340	52.8	550	79.8	5150	11350	40	24.9
650/45-22.5	20	TT/TL	AG 20.00	45	56	635	25.0	1153	45.4	500	72.5	3750	8270	40	24.9
700/45-22.5	20	TT/TL	AG 24.00	42	53	710	28.0	1170	46.1	550	79.8	4625	10200	40	24.9
700/50-26.5	20	TT/TL	AG 24.00	48	60	710	28.0	1340	52.8	550	79.8	5600	12350	40	24.9
710/40-22.5	20	TT/TL	AG 24.00	42	53	710	28.0	1170	46.1	550	79.8	4625	10200	40	24.9
710/40-24.5	20	TT/TL	AG 24.00	48	60	710	28.0	1230	48.4	550	79.8	4875	10750	40	24.9
710/45-26.5	20	TT/TL	AG 24.00	48	60	710	28.0	1340	52.8	550	79.8	5600	12350	40	24.9
710/55-28.5	24	TT/TL	AG 24.00	49	61	710	28.0	1525	60.0	600	87.0	8000	17640	40	24.9
750/55-26.5	24	TT/TL	AG 24.00	49	61	750	29.5	1485	58.5	600	87.0	8500	18740	40	24.9
780/50-28.5	24	TT/TL	AG 26.00	49	61	780	30.7	1525	60.0	600	87.0	8500	18740	40	24.9
800/40-26.5	20	TT/TL	AG 28.00	48	60	800	31.5	1340	52.8	550	79.8	6000	13230	40	24.9



TRC02

## FLOTATION TIRE TRC02

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
						(mm)	inch	(mm)	inch						
400/60-15.5	16	TL	13.00	18	23	404	16	874	34.4	400	58	3250	7165	40	25



T322

T324

T325

HT326

## LPT BIAS TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
					(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)
							(mm)	inch	(mm)	inch				
7-14.5 ST	12	TL	T322	6.00	6	8	194	7.6	680	26.8	690	100	1059	2335
8-14.5 ST	14	TL	T322	6.00	6	8	203	8.0	707	27.8	790	115	1405	3100

## MOBILE HOME TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
					(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)
							(mm)	inch	(mm)	inch				
8-14.5	14	TL	T322	6.00	6	8	194	7.6	680	26.8	790	115	1405	3100
8-14.5	14	TL	T322	6.00	6	8	194	7.6	680	26.8	790	115	1585	3500
8-14.5	16	TL	T322	6.00	6	8	194	7.6	680	26.8	790	115	1585	3500
8-14.5	14	TL	T322	6.00	6	8	203	8.0	707	27.8	790	115	1405	3100
9-14.5	14	TL	T324	7.00	9	11	241	9.5	711	28.0	790	115	1590	3500
215/60D14.5	14	TL	T325	6.00	6	8	196	7.7	628	24.7	760	110	1405	3100
235/60D14.5	14	TL	T325	7.00	7	9	230	9.1	673	26.5	760	110	1590	3500

## SPECIAL TRAILER TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
				(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)
						(mm)	inch	(mm)	inch				
ST175/80D13	6	TL	5.00	6.5	8	177	7.0	610	24.0	350/*350	50/*50	545/*615	1200/*1360
ST205/65D14	6	TL	5.50	7.5	9	192	7.6	620	24.4	350/*350	50/*50	800/*710	1760/*1570
ST205/75D14	6	TL	5.50	8	10	203	8.0	664	26.1	350/*350	50/*50	710/*800	1570/*1760
ST205/75D15	6	TL	5.50	8	10	203	8.0	689	27.1	350/*350	50/*50	730/*825	1610/*1820
ST225/75D15	8	TL	6.00	8	10	223	8.8	719	28.3	450/*450	65/*65	1000/*1150	2200/*2540



HT327

HT328

HT329

HT330

## SPECIAL TRAILER TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		
					(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)	
							(mm)	inch	(mm)	inch					
16.5x6.5-8	4	TL	HT327	5.375	5.5	7	166	6.5	418	16.5	310	45	280	620	
16.5x6.5-8	6	TL		5.375	5.5	7	166	6.5	418	16.5	480	70	320	620	
20.5x8.0-10	4	TL		6.00	7	9	203	8.0	518	20.4	240	35	412	910	
20.5x8.0-10	6	TL		6.00	7	9	203	8.0	518	20.4	340	50	501	1105	
20.5x8.0-10	8	TL		6.00	7	9	203	8.0	518	20.4	480	70	603	1330	
20.5x8.0-10	10	TL		6.00	7	9	203	8.0	518	20.4	620	90	696	1535	
20.5x8.0-10	12	TL		6.00	7	9	203	8.0	518	20.4	650	95	787	1735	
22.5x8.0-12	12	TL		6.00	7.5	9	222	8.7	572	22.5	755	110	895	1980	
16.5x6.5-8	4	TL		HT328	5.375	7	9	166	6.5	418	16.5	310	45	280	620
16.5x6.5-8	6	TL			5.375	7	9	166	6.5	418	16.5	480	70	320	705
18.5x8.5-8	4	TL	7.00		7	9	213	8.4	462	18.2	240	35	349	770	
18.5x8.5-8	6	TL	7.00		7	9	213	8.4	462	18.2	340	50	500	1100	
20.5x8.0-10	4	TL	6.00		7	9	203	8.0	518	20.4	240	35	412	910	
20.5x8.0-10	6	TL	6.00		7	9	203	8.0	518	20.4	340	50	501	1105	
20.5x8.0-10	8	TL	6.00		7	9	203	8.0	518	20.4	480	70	603	1330	
20.5x8.0-10	10	TL	6.00		7	9	203	8.0	518	20.4	620	90	696	1535	
20.5x8.0-10	12	TL	6.00		7	9	203	8.0	518	20.4	650	95	787	1735	
4.80-8	4	TL	HT329		3.75	5.5	7	121	4.8	423	16.7	410	60	267	590
4.80-8	6	TL		3.75	5.5	7	121	4.8	423	16.7	620	90	345	760	
5.70-8	4	TL		4.50	6	8	146	5.7	469	18.5	340	50	325	715	
5.70-8	6	TL		4.50	6	8	146	5.7	469	18.5	520	75	412	910	
5.70-8	8	TL		4.50	6	8	146	5.7	469	18.5	690	100	487	1070	
5.70-8	8	TL		4.50	6	8	146	5.7	469	18.5	690	100	490	1075	
4.80-12	4	TL		3.75	5.5	7	121	4.8	524	20.6	410	60	267	590	
4.80-12	6	TL		3.75	5.5	7	121	4.8	524	20.6	620	90	450	990	
5.30-12	4	TL		4.25	6	8	135	5.3	548	21.6	380	55	387	855	
5.30-12	6	TL		4.25	6	8	135	5.3	548	21.6	550	80	475	1050	

## GOLF CART TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
					(mm)	(32nd)	Section Width		Overall Diameter		(kPa)	(psi)	(kg)	(Lbs)
							(mm)	inch	(mm)	inch				
18x8.5-8	4	TL	HT328	7	6	8	213	8.4	445	17.5	150	22	370	815



T236

T237

T238

E116

## TRAILER TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)
<b>T236</b>													
ST205/90D15	10	TL	5J	9.5	12	200	7.9	750	29.5	550*550	80*80	1320/1150	2910/2540
ST225/90D16	10	TL	6J	9.5	12	215	8.5	805	31.7	520*520	75*75	1560/3440	1370/3020
<b>T237</b>													
7.00-15	8	TL	5.50F	11	14	200	7.9	750	29.5	410/*410	60/*60	825/*925	1820/*2040
7.00-15	10	TL	5.50F	11	14	200	7.9	750	29.5	520/*520	75/*75	925/*1060	2040/*2335
7.50-16	10	TL	6.00G	12	15	215	8.5	805	31.7	520/*520	75/*75	1120/*1250	2470/*2755
7.50-16	12	TL	6.00G	12	15	215	8.5	805	31.7	630/*630	91/*91	1400/*1250	3085/*2755
<b>T238</b>													
ST205/90D15	10	TL	5J	9.5	12	200	7.9	750	29.5	550*550	80*80	1320/1150	2910/2540
ST225/90D16	10	TL	6J	9.5	12	215	8.5	805	31.7	520*520	75*75	1560/3440	1370/3020
<b>E116</b>													
7.50-16	10	TL	6.00G	11	14	215	8.5	805	31.7	520/*520	75/*75	1120/*1250	2470/*2755
7.50-16	12	TL	6.00G	11	14	215	8.5	805	31.7	630/*630	91/*91	1400/*1250	3085/*2755
ST225/90D16	10	TL	6J	9.5	12	215	8.5	805	31.7	520*520	75*75	1560/3440	1370/3020



NT161

T332

T311

## BIAS TRUCK TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		
					(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	
<b>NT161</b>															
N78-15LT	6	TL	T161	7.00	22	28	230	9.1	785	30.9	310	45	872	1920	
P78-16LT	6	TL	T161	6.50	23	29	219	8.6	830	32.7	310	45	990	2180	
<b>T332</b>															
7.50-17	10	TL	T332	6.00	10.5	13	215	8.5	859	33.8	550/*620	80/*90	1260/*1440	2780/*3170	
<b>T311</b>															
10.00-20	14	TT	T311	7.50	11.5	14	278	10.9	1054	41.5	620/*690	90/*100	2430/*2800	5355/*6175	



T321

## TRAILER TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
					(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)
10.00-20	12	TT	T321	7.5	11.5	14	278	10.9	1054	41.5	520/*590	75/*85	2180/*2500	4805/*5510
10.00-20	14	TT	T321	7.5	11.5	14	278	10.9	1054	41.5	620/*690	90/*100	2430/*2800	5355/*6175
11-22.5	12	TL	T321	8.25	11.5	14	279	11.0	1054	41.5	520/*590	75/*85	2180/*2500	4805/*5510
11-22.5	14	TL	T321	8.25	11.5	14	279	11.0	1054	41.5	620/*690	90/*100	2430/*2800	5840/*6610



K72



K-305

## BIAS TRUCK TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth (mm)	New tire inflated dimensions		Pressure		Max. Load	
						Section Width	Overall Diameter	(kPa)	(psi)	(kg)	(Lbs)
						(mm)	(mm)				
7.00-15	10	TL	K72	5.50F	11	200	750	520/*520	75/*75	925/*1060	2040/*2335
7.50-16	10	TL	K72	6.00G	12	215	805	520/*520	75/*75	1120/*1250	2470/*2755
8.25-20	10	TT	K72	6.50	12	236	974	530/*600	77/*87	1600/*1850	3520/*4075
9.00-20	10	TT	K72	7.00	12	259	1018	490/*560	71/*81	1850/*2120	4075/*4670
10.00-20	12	TT	K72	7.50	13.5	278	1055	520/*590	75/*85	2180/*2500	4805/*5510
8.25-20	10	TT	K-305	6.50	19	236	974	530/*600	77/*87	1600/*1850	3520/*4075
9.00-20	10	TT	K-305	7.00	21	259	1018	490/*560	71/*81	1850/*2120	4075/*4670
10.00-20	12	TT	K-305	7.50	20.5	278	1055	520/*590	75/*85	2180/*2500	4805/*5510



KS601



KS602

## MINING TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth (mm)	New tire inflated dimensions		Pressure		Max. Load	
						Section Width	Overall Diameter	(kPa)	(psi)	(kg)	(Lbs)
						(mm)	(mm)				
7.50-16	14	TT	KS601	6.00G	22	215	805	730/*730	106/*106	1320/*1500	2910/*3300
10.00-20	16	TT	KS601	7.50	25	278	1073	740/*810	105/*115	2650/*3000	5840/*6610
8.25-16	16	TT	KS602	6.50H	14	235	867	730/*730	106/*106	1600/*1800	3520/*3960



L-5S  
L-5SA  
L-5SL

## UNDERGROUND MINING TIRES

Size	P.R.	TT/TL	PATTERN	Rim	New tire inflated dimensions			Pressure (kPa)	Max. Load (kg)
					Tread Depth	Section Width	Overall Diameter		
					(mm)	(mm)	(mm)		
29.5-29	40	TL	L-5S	25.00/3.5	110	750	2025	625	23600
29.5-25	34	TL	L-5S	25.00/3.5	110	750	1920	525	19800
26.5-25	36	TL	L-5S/L-5SL	22.00/3.0	100/80	675	1800	625	18500
18.00-25	32	TL	L-5S	13.00/2.5	85	526	1673	750	15000
17.5-25	24	TT/TL	L-5S	14.00/1.5	82	445	1400	675	9000
17.5-25	20	TT/TL	L-5S/L-5SL/L-5SA	14.00/1.5	82/63.5/45.5	445	1400	575	8250
14.00-24	28	TT	L-5S/L-5SL	10	77/63.5	386/375	1417/1420	1000/925	13500/10000
12.00-24	24	TT	L-5S/L-5SL	8.5	55/47	333	1300	1000	10250
12.00-20	28	TT	L-5S	8.5	67	340	1173	1030	8620
12.00-20	20	TT	L-5SA	8.5	57	315	1145	900	6325
10.00-20	18	TT	L-5S	7.5	58	300	1097	1000	7255
8.25-15	24	TT	L-5S	6.5	52	260	864	1030	6070

## BIAS TRUCK TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth (mm)	New tire inflated dimensions		Pressure		Max. Load	
						Section Width	Overall Diameter	(kPa)	(psi)	(kg)	(Lbs)
						(mm)	(mm)				
6.00-13	8	TT	HIW/LUG	4.50B	9	170	655	420/*420	61/*61	580/*650	1280/*1430
6.00-14	8	TT	HIW/LUG	41/2J	9	170	680	420/*420	61/*61	600/*690	1320/*1520
6.00-14	10	TT	HIW	41/2J	9	170	680	530/*530	77/*77	710/*800	1565/*1760
6.00-14	10	TT	HIW	41/2J	15.5	170	680	530/*530	77/*77	710/*800	1565/*1760
6.00-15	10	TT	HIW	4.50E	15	170	705	530/*530	77/*77	825/*930	1820/*2340
6.50-14	8	TT	HIW	41/2J	9	180	705	420/*420	61/*61	690/*785	1520/*1730
6.50-15	10	TT	HIW	4.50E	10	180	730	530/*530	77/*77	840/*950	1850/*2090
6.50-16	12	TT	HIW/LUG	5.50F	11	185	750	630/*630	91/*91	925/*1060	2040/*2335
7.00-15	12	TT	HIW	5.50F	9.5	200	750	630/*630	91/*91	1030/*1150	2265/*2530
7.00-16	14	TT	HIW/LUG	5.50F	11	200	775	730/*730	106/*106	1180/*1320	2600/*2910
7.50-16	14	TT	HIW/LUG	6.00G	11	215	805	730/*730	106/*106	1320/*1500	2910/*3300
8.25-16	14	TT	HIW/LUG	6.50H	13	235	855	630/*630	91/*91	1500/*1700	3305/*3745
7.50-20	14	TT	HIW/LUG	6.00	12.5	215	935	740/*810	105/*115	1650/*1900	3640/*4190
8.25-20	14	TT	HIW/LUG	6.50	12.5	236	974	740/*810	105/*115	1950/*2240	4410/*4940
9.00-20	14	TT	HIW/LUG	7.00	14	259	1018	690/*760	100/110	2300/*2575	5070/*5675
10.00-20	14	TT	HIW/LUG	7.50	14	278	1055	620/*690	90/*100	2430/*2800	5355/*6175
10.00-20	16	TT	HIW/LUG	7.50	14	278	1055	720/*790	105/*115	2650/*3000	5840/*6610
11.00-20	16	TT	LUG	8.00	16	293	1085	720/*790	105/*115	2900/*3350	6395/*7390
11.00-20	18	TT	LUG	8.00	16	293	1085	840/*910	122/*132	3150/*3650	6945/*8045
12.00-20	20/18	TT	HIW/LUG	8.50	23	315	1125	810/*1125	115/*165	3450/*4000	7590/*8800